



US006791859B2

(12) **United States Patent**
Hush et al.

(10) **Patent No.:** **US 6,791,859 B2**
(45) **Date of Patent:** **Sep. 14, 2004**

(54) **COMPLEMENTARY BIT PCRAM SENSE AMPLIFIER AND METHOD OF OPERATION**

FOREIGN PATENT DOCUMENTS

(75) Inventors: **Glen Hush**, Boise, ID (US); **Jake Baker**, Meridian, ID (US)

EP	1 109 170 A2	6/2001
JP	56126916	10/1998
WO	WO 97/48032	12/1997
WO	WO 99/28914	6/1999
WO	WO 00/48196	8/2000
WO	WO 02/21542	3/2002

(73) Assignee: **Micron Technology, Inc.**, Boise, ID (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

OTHER PUBLICATIONS

(21) Appl. No.: **09/988,627**

Axon Technologies Corporation, Technology Description: *Programmable Metalization Cell(PMC)*, pp. 1-6 (Pre-May 2000).

(22) Filed: **Nov. 20, 2001**

Helbert et al., *Intralevel hybrid resist process with submicron capability*, SPIE vol. 333 Submicron Lithography, pp. 24-29 (1982).

(65) **Prior Publication Data**

US 2003/0095426 A1 May 22, 2003

Hilt, Dissertation: *Materials characterization of Silver Chalcogenide Programmable Metalization Cells*, Arizona State University, pp. Title page-114 (UMI Company, May 1999).

(51) **Int. Cl.**⁷ **G11C 17/00**

(52) **U.S. Cl.** **365/100**; 365/203; 365/185.25; 365/204; 365/226

(58) **Field of Search** 365/100, 203, 365/185.25, 204, 226, 158, 171, 189.07, 222

Hirose et al., *High Speed Memory Behavior and Reliability of an Amorphous As₂S₃ Film Doped Ag*, Phys. Stat. Sol. (a) 61, pp. 87-90 (1980).

(56) **References Cited**

(List continued on next page.)

U.S. PATENT DOCUMENTS

3,622,319 A	11/1971	Sharp
3,743,847 A	7/1973	Boland
4,112,512 A	9/1978	Arzubi et al.
4,269,935 A	5/1981	Masters et al.
4,312,938 A	1/1982	Drexler et al.
4,316,946 A	2/1982	Masters et al.
4,320,191 A	3/1982	Yoshikawa et al.
4,405,710 A	9/1983	Balasubramanyam et al.
4,419,421 A	12/1983	Wichelhaus et al.
4,499,557 A	2/1985	Holmberg et al.
4,671,618 A	6/1987	Wu et al.
4,795,657 A	1/1989	Formigoni et al.
4,800,526 A	1/1989	Lewis
4,847,674 A	7/1989	Sliwa et al.
5,177,567 A	1/1993	Klersy et al.
5,219,788 A	6/1993	Abernathey et al.


(List continued on next page.)

Primary Examiner—Richard Elms
Assistant Examiner—N. Nguyen
(74) *Attorney, Agent, or Firm*—Dickstein Shapiro Morin & Oshinsky LLP

(57) **ABSTRACT**

A method and apparatus is disclosed for sensing the resistance state of a Programmable Conductor Random Access Memory (PCRAM) element using complementary PCRAM elements, one holding the resistance state being sensed and the other holding a complementary resistance state. A sense amplifier detects voltages discharging through the high and low resistance elements to determine the resistance state of an element being read.

13 Claims, 6 Drawing Sheets



U.S. PATENT DOCUMENTS

5,238,862 A	8/1993	Blalock et al.	
5,272,359 A	12/1993	Nagasubramanian et al.	
5,314,772 A	5/1994	Kozicki	
5,315,131 A	5/1994	Kishimoto et al.	
5,350,484 A	9/1994	Gardner et al.	
5,360,981 A	11/1994	Owen et al.	
5,500,532 A	3/1996	Kozicki et al.	
5,512,328 A	4/1996	Yoshimura et al.	
5,512,773 A	4/1996	Wolf et al.	
5,699,293 A	* 12/1997	Tehrani et al.	365/158
5,726,083 A	3/1998	Takaishi	
5,751,012 A	5/1998	Wolstenholme et al.	
5,761,115 A	6/1998	Kozicki et al.	
5,789,277 A	8/1998	Zahorik et al.	
5,814,527 A	9/1998	Wolstenholme et al.	
5,818,749 A	10/1998	Harshfield	
5,841,150 A	11/1998	Gonzalez et al.	
5,846,889 A	12/1998	Harbison et al.	
5,851,882 A	12/1998	Harshfield	
5,869,843 A	2/1999	Harshfield	
5,883,827 A	3/1999	Morgan	
5,896,312 A	4/1999	Kozicki et al.	
5,914,893 A	6/1999	Kozicki et al.	
5,920,788 A	7/1999	Reinberg	
5,936,880 A	* 8/1999	Payne	365/148
5,936,882 A	* 8/1999	Dunn	365/158
5,998,066 A	12/1999	Block et al.	
6,031,287 A	2/2000	Harshfield	
6,072,716 A	6/2000	Jacobson et al.	
6,077,729 A	6/2000	Harshfield	
6,084,796 A	7/2000	Kozicki et al.	
6,117,720 A	9/2000	Harshfield	
6,143,604 A	11/2000	Chiang et al.	
6,177,338 B1	1/2001	Liaw et al.	
6,191,972 B1	2/2001	Miura et al.	
6,191,989 B1	2/2001	Luk et al.	
6,236,059 B1	5/2001	Wolstenholme et al.	
6,243,311 B1	6/2001	Keeth	
6,297,170 B1	10/2001	Gabriel et al.	
6,300,684 B1	10/2001	Gonzalez et al.	
6,314,014 B1	* 11/2001	Lowrey et al.	365/100
6,316,784 B1	11/2001	Zahorik et al.	
6,329,606 B1	12/2001	Freyman et al.	
6,348,365 B1	2/2002	Moore et al.	
6,350,679 B1	2/2002	McDaniel et al.	
6,376,284 B1	4/2002	Gonzalez et al.	
6,388,324 B2	5/2002	Kozicki et al.	
6,391,688 B1	5/2002	Gonzalez et al.	
6,414,376 B1	7/2002	Thakur et al.	
6,418,049 B1	7/2002	Kozicki et al.	
6,420,725 B1	7/2002	Harshfield	
6,423,628 B1	7/2002	Li et al.	
6,440,837 B1	8/2002	Harshfield	
6,462,981 B2	10/2002	Numata et al.	
6,469,364 B1	10/2002	Kozicki	
6,473,332 B1	10/2002	Ignatiev et al.	
6,487,106 B1	11/2002	Kozicki	
6,490,190 B1	* 12/2002	Ramcke et al.	365/158
2002/0000666 A1	1/2002	Kozicki et al.	
2000/0072188	6/2002	Gilton	
2002/0106849 A1	8/2002	Moore	
2002/0123169 A1	9/2002	Moore et al.	
2002/0123170 A1	9/2002	Moore et al.	
2002/0123248 A1	9/2002	Moore et al.	
2002/0127886 A1	9/2002	Moore et al.	
2002/0132417 A1	9/2002	Li	
2002/0160551 A1	10/2002	Harshfield	
2002/0163828 A1	11/2002	Krieger et al.	
2002/0168820 A1	11/2002	Kozicki et al.	
2002/0168852 A1	11/2002	Harshfield et al.	
2002/0190289 A1	12/2002	Harshfield et al.	
2002/0190350 A1	12/2002	Kozicki	
2003/0001229 A1	1/2003	Moore et al.	
2003/0027416 A1	2/2003	Moore	
2003/0032254 A1	2/2003	Gilton	
2003/0035314 A1	2/2003	Kozicki	
2003/0035315 A1	2/2003	Kozicki	
2003/0038301 A1	2/2003	Moore	
2003/0043631 A1	3/2003	Gilton et al.	
2003/0045049 A1	3/2003	Campbell et al.	
2003/0045054 A1	3/2003	Campbell et al.	
2003/0047765 A1	3/2003	Campbell	
2003/0047772 A1	3/2003	Li	
2003/0048519 A1	3/2003	Kozicki	
2003/0049912 A1	3/2003	Campbell et al.	
2003/0068861 A1	4/2003	Li et al.	
2003/0068862 A1	4/2003	Li et al.	
2003/0095426 A1	5/2003	Hush et al.	
2003/0096497 A1	5/2003	Moore et al.	
2003/0107105 A1	6/2003	Kozicki	
2003/0117831 A1	6/2003	Hush	
2003/0128612 A1	7/2003	Moore et al.	
2003/0137869 A1	7/2003	Kozicki	
2003/0143782 A1	7/2003	Gilton et al.	
2003/0156447 A1	8/2003	Kozicki	
2003/0156463 A1	8/2003	Casper et al.	

OTHER PUBLICATIONS

Holmquist et al., *Reaction and Diffusion in Silver-Arsenic Chalcogenide Glass Systems*, 62 J. Amer. Ceram. Soc., No. 3-4, pp. 183-188 (Mar.-Apr. 1979).

Huggett et al., *Development of silver sensitized germanium selenide photoresist by reactive sputter etching in SF₆*, 42 Appl. Phys. Lett., No. 7, pp. 592-594 (Apr. 1983).

Kawaguchi et al., *Mechanism of photosurface deposition*, 164-166 J. Non-Cryst. Solids, pp. 1231-1234 (1993).

Kolobov and Elliott, *Photodoping of Amorphous Chalcogenides by Metals*, Advances in Physics, vol. 40, No. 5, 625-684 (1991).

Kozicki, et al., "Applications of Programmable Resistance Changes in Metal-doped Chalcogenides", Proceedings of the 1999 Symposium on Solid State Ionic Devices, Editors—E.D. Wachsman et al., The Electrochemical Society, Inc., 1-12 (1999).

Kozicki, et al., *Nanoscale effects in devices based on chalcogenide solid solutions*, Superlattices and Microstructures, 27, 485-488 (2000).

Kozicki, et al., *Nanoscale phase separation in Ag-Ge-Se glasses*, Microelectronic Engineering, vol. 63/1-3, 155-159 (2002).

M.N. Kozicki and M. Mitkova, *Silver incorporation in thin films of selenium rich Ge-Se glasses*, Proceedings of the XIX International Congress on Glass, Society for Glass Technology, 226-227 (2001).

McHardy et al., *The dissolution of metals in amorphous chalcogenides and the effects of electron and ultraviolet radiation*, 20 J. Phys. C.: Solid State Phys., pp. 4055-4075 (1987)f.

Owen et al., *Metal-Chalcogenide Photoresists for High Resolution Lithography and Sub-Micron Structures*, Nanostructure Physics and Fabrication, pp. 447-451 (M. Reed ed. 1989).

Shimizu et al., *The Photo-Erasable Memory Switching Effect of Ag Photo-Doped Chalcogenide Glasses*, 46 B. Chem Soc. Japan, No. 12, pp. 3662-3365 (1973).

- Scheuerlein R. et al., *A 10ns Read and Write Non-Volatile Memory Array Using a Magnetic Tunnel Junction and FET Switch in each Cell*, Digest of Technical Papers. 2000 IEEE Int'l Solid-State Circuits Conference, Session 7, Paper TA 7.2, Feb. 8, 2000, pp. 128–129.
- Abdel-Alt, A.; Elshafie, A.; Elhawary, M.M., DC electric-field effect in bulk and thin-film Ge₅As₃₈Te₅₇ chalcogenide glass, *Vacuum* 59 (2000) 845–853.
- Adler, D.; Moss, S.C., Amorphous memories and bistable switches, *J. Vac. Sci. Technol.* 9 (1972) 1182–1189.
- Adler, D.; Henisch, H.K.; Mott, S.N., The mechanism of threshold switching in amorphous alloys, *Rev. Mod. Phys.* 50 (1978) 209–220.
- Afifi, M.A.; Labib, H.H.; El-Fazary, M.H.; Fadel, M., Electrical and thermal properties of chalcogenide glass system Se₇₅Ge_{25-x}Sb_x, *Appl. Phys. A* 55 (1992) 167–169.
- Afifi, M.A.; Labib, H.H.; Fouad, S.S.; El-Shazly, A.A., Electrical & thermal conductivity of the amorphous semiconductor GexSe_{1-x}, *Egypt. J. Phys.* 17 (1986) 335–342.
- Alekperova, Sh.M.; Gadzhieva, G.S., Current-Voltage characteristics of Ag₂Se single crystal near the phase transition, *Inorganic Materials* 23 (1987) 137–139.
- Aleksiejunas, A.; Cesnys, A., Switching phenomenon and memory effect in thin-film heterojunction of polycrystalline selenium-silver selenide, *Phys. Stat. Sol. (a)* 19 (1973) K169–K171.
- Angell, C.A., Mobile ions in amorphous solids, *Annu. Rev. Phys. Chem.* 43 (1992) 693–717.
- Aniya, M., Average electronegativity, medium-range-order, and ionic conductivity in superionic glasses, *Solid state Ionics* 136–137 (2000) 1085–1089.
- Asahara, Y.; Izumitani, T., Voltage controlled switching in Cu-As-Se compositions, *J. Non-Cryst. Solids* 11 (1972) 97–104.
- Asokan, S.; Prasad, M.V.N.; Parthasarathy, G.; Gopal, E.S.R., Mechanical and chemical thresholds in IV-VI chalcogenide glasses, *Phys. Rev. Lett.* 62 (1989) 808–810.
- Baranovskii, S.D.; Cordes, H., On the conduction mechanism in ionic glasses, *J. Chem. Phys.* 111 (1999) 7546–7557.
- Belin, R.; Taillades, G.; Pradel, A.; Ribes, M., Ion dynamics in superionic chalcogenide glasses: complete conductivity spectra, *Solid state Ionics* 136–137 (2000) 1025–1029.
- Belin, R.; Zerouale, A.; Pradel, A.; Ribes, M., Ion dynamics in the argyrodite compound Ag₇GeSe₅I: non-Arrhenius behavior and complete conductivity spectra, *Solid State Ionics* 143 (2001) 445–455.
- Benmore, C.J.; Salmon, P.S., Structure of fast ion conducting and semiconducting glassy chalcogenide alloys, *Phys. Rev. Lett.* 73 (1994) 264–267.
- Bernede, J.C., Influence du metal des electrodes sur les caracteristiques courant-tension des structures M-Ag₂Se-M, *Thin solid films* 70 (1980) L1–L4.
- Bernede, J.C., Polarized memory switching in MIS thin films, *Thin Solid Films* 81 (1981) 155–160.
- Bernede, J.C., Switching and silver movements in Ag₂Se thin films, *Phys. Stat. Sol. (a)* 57 (1980) K101–K104.
- Bernede, J.C.; Abachi, T., Differential negative resistance in metal/insulator/metal structures with an upper bilayer electrode, *Thin solid films* 131 (1985) L61–L64.
- Bernede, J.C.; Conan, A.; Fousenan't, E.; El Bouchairi, B.; Goureaux, G., Polarized memory switching effects in Ag₂Se/Se/M thin film sandwiches, *Thin solid films* 97 (1982) 165–171.
- Bernede, J.C.; Khelil, A.; Kettaf, M.; Conan, A., Transition from S- to N-type differential negative resistance in Al-Al₂O₃-Ag_{2-x}Se_{1+x} thin film structures, *Phys. Stat. Sol. (a)* 74 (1982) 217–224.
- Bondarev, V.N.; Pikhitsa, P.V., A dendrite model of current instability in RbAg₄I₅, *Solid State Ionics* 70/71 (1994) 72–76.
- Boolchand, P., The maximum in glass transition temperature (T_g) near x=1/3 in GexSe_{1-x} Glasses, *Asian Journal of Physics* (2000) 9, 709–72.
- Boolchand, P.; Bresser, W.J., Mobile silver ions and glass formation in solid electrolytes, *Nature* 410 (2001) 1070–1073.
- Boolchand, P.; Georgiev, D.G.; Goodman, B., Discovery of the Intermediate Phase in Chalcogenide Glasses, *J. Optoelectronics and Advanced Materials*, 3 (2001), 703.
- Boolchand, P.; Selvanathan, D.; Wang, Y.; Georgiev, D.G.; Bresser, W.J., Onset of rigidity in steps in chalcogenide glasses, *Properties and Applications of Amorphous Materials*, M.F. Thorpe and Tichy, L. (eds.) Kluwer Academic Publishers, the Netherlands, 2001, pp. 97–132.
- Boolchand, P.; Enzweiler, R.N.; Tenhover, M., Structural ordering of evaporated amorphous chalcogenide alloy films: role of thermal annealing, *Diffusion and Defect Data vol. 53–54* (1987) 415–420.
- Boolchand, P.; Grothaus, J.; Bresser, W.J.; Suranyi, P., Structural origin of broken chemical order in a GeSe₂ glass, *Phys. Rev. B* 25 (1982) 2975–2978.
- Boolchand, P.; Grothaus, J.; Phillips, J.C., Broken chemical order and phase separation in GexSe_{1-x} glasses, *Solid state comm.* 45 (1983) 183–185.
- Boolchand, P.; Bresser, W.J., Compositional trends in glass transition temperature (T_g), network connectivity and nanoscale chemical phase separation in chalcogenides, *Dept. of ECECS, Univ. Cincinnati* (Oct. 28, 1999) 45221–0030.
- Boolchand, P.; Grothaus, J., Molecular Structure of Melt-Quenched GeSe₂ and GeS₂ glasses compared, *Proc. Int. Conf. Phys. Semicond.* (Eds. Chadi and Harrison) 17th (1985) 833–36.
- Bresser, W.; Boolchand, P.; Suranyi, P., Rigidity percolation and molecular clustering in network glasses, *Phys. Rev. Lett.* 56 (1986) 2493–2496.
- Bresser, W.J.; Boolchand, P.; Suranyi, P.; de Neufville, J.P., Intrinsically broken chalcogen chemical order in stoichiometric glasses, *Journal de Physique* 42 (1981) C4–193–C4–196.
- Bresser, W.J.; Boolchand, P.; Suranyi, P.; Hernandez, J.G., Molecular phase separation and cluster size in GeSe₂ glass, *Hyperfine Interactions* 27 (1986) 389–392.
- Cahen, D.; Gilet, J.-M.; Schmitz, C.; Chernyak, L.; Gartsman, K.; Jakubowicz, A., Room-Temperature, electric field induced creation of stable devices in CuInSe₂ Crystals, *Science* 258 (1992) 271–274.
- Chatterjee, R.; Asokan, S.; Titus, S.S.K., Current-controlled negative-resistance behavior and memory switching in bulk As-Te-Se glasses, *J. Phys. D: Appl. Phys.* 27 (1994) 2624–2627.
- Chen, C.H.; Tai, K.L., Whisker growth induced by Ag photodoping in glassy GexSe_{1-x} films, *Appl. Phys. Lett.* 37 (1980) 1075–1077.
- Chen, G.; Cheng, J., Role of nitrogen in the crystallization of silicon nitride-doped chalcogenide glasses, *J. Am. Ceram. Soc.* 82 (1999) 2934–2936.

- Chen, G.; Cheng, J.; Chen, W., Effect of Si₃N₄ on chemical durability of chalcogenide glass, *J. Non-Cryst. Solids* 220 (1997) 249–253.
- Cohen, M.H.; Neale, R.G.; Paskin, A., A model for an amorphous semiconductor memory device, *J. Non-Cryst. Solids* 8–10 (1972) 885–891.
- Croitoru, N.; Lazarescu, M.; Popescu, C.; Telnic, M.; and Vescan, L., Ohmic and non-ohmic conduction in some amorphous semiconductors, *J. Non-Cryst. Solids* 8–10 (1972) 781–786.
- Dalven, R.; Gill, R., Electrical properties of beta-Ag₂Te and beta-Ag₂Se from 4.2 to 300K, *J. Appl. Phys.* 38 (1967) 753–756.
- Davis, E.A., *Semiconductors without form*, Search 1 (1970) 152–155.
- Dearnaley, G.; Stoneham, A.M.; Morgan, D.V., Electrical phenomena in amorphous oxide films, *Rep. Prog. Phys.* 33 (1970) 1129–1191.
- Dejus, R.J.; Susman, S.; Volin, K.J.; Montague, D.G.; Price, D.L., Structure of Vitreous Ag–Ge–Se, *J. Non-Cryst. Solids* 143 (1992) 162–180.
- den Boer, W., Threshold switching in hydrogenated amorphous silicon, *Appl. Phys. Lett.* 40 (1982) 812–813.
- Drusedau, T.P.; Panckow, A.N.; Klabunde, F., The hydrogenated amorphous silicon/nanodisperse metal (SIMAL) system—Films of unique electronic properties, *J. Non-Cryst. Solids* 198–200 (1996) 829–832.
- El Bouchairi, B.; Bernede, J.C.; Burgaud, P., Properties of Ag₂–xSe_{1+x/n}–Si diodes, *Thin Solid Films* 110 (1983) 107–113.
- El Gharras, Z.; Bourahla, A.; Vautier, C., Role of photoinduced defects in amorphous Ge_xSe_{1-x} photoconductivity, *J. Non-Cryst. Solids* 155 (1993) 171–179.
- El Ghrandi, R.; Calas, J.; Galibert, G.; Averous, M., Silver photodissolution in amorphous chalcogenide thin films, *Thin Solid Films* 218 (1992) 259–273.
- El Ghrandi, R.; Calas, J.; Galibert, G., Ag dissolution kinetics in amorphous GeSe_{5.5} thin films from “In-situ” resistance measurements vs time, *Phys. Stat. Sol. (a)* 123 (1991) 451–460.
- El-kady, Y.L., The threshold switching in semiconducting glass (Ge₂₁Se₁₇Te₆₂), *Indian J. Phys.* 70A (1996) 507–516.
- Elliott, S.R., A unified mechanism for metal photodissolution in amorphous chalcogenide materials, *J. Non-Cryst. Solids* 130 (1991) 85–97.
- Elliott, S.R., Photodissolution of metals in chalcogenide glasses: A unified mechanism, *J. Non-Cryst. Solids* 137–138 (1991) 1031–1034.
- Elsamanoudy, M.M.; Hegab, N.A.; Fadel, M., Conduction mechanism in the pre-switching state of thin films containing Te As Ge Si, *Vacuum* 46 (1995) 701–707.
- El-Zahad, H.; El-Korashy, A., Influence of composition on the electrical and optical properties of Ge₂₀BixSe_{80-x} films, *Thin Solid Films* 376 (2000) 236–240.
- Fadel, M., Switching phenomenon in evaporated Se–Ge–As thin films of amorphous chalcogenide glass, *Vacuum* 44 (1993) 851–855.
- Fadel, M.; El-Shair, H.T., Electrical, thermal and optical properties of Se₇₅Ge₇Sb₁₈, *Vacuum* 43 (1992) 253–257.
- Feng, X.; Bresser, W.J.; Boolchand, P., Direct evidence for stiffness threshold in Chalcogenide glasses, *Phys. Rev. Lett.* 78 (1997) 4422–4425.
- Feng, X.; Bresser, W.J.; Zhang, M.; Goodman, B.; Boolchand, P., Role of network connectivity on the elastic, plastic and thermal behavior of covalent glasses, *J. Non-Cryst. Solids* 222 (1997) 137–143.
- Fischer-Colbrie, A.; Bienenstock, A.; Fuoss, P.H.; Marcus, M.A., Structure and bonding in photodiffused amorphous Ag–GeSe₂ thin films, *Phys. Rev. B* 38 (1988) 12388–12403.
- Fleury, G.; Hamou, A.; Viger, C.; Vautier, C., Conductivity and crystallization of amorphous selenium, *Phys. Stat. Sol. (a)* 64 (1981) 311–316.
- Fritzsche, H., Optical and electrical energy gaps in amorphous semiconductors, *J. Non-Cryst. Solids* 6 (1971) 49–71.
- Fritzsche, H., Electronic phenomena in amorphous semiconductors, *Annual Review of Materials Science* 2 (1972) 697–744.
- Gates, B.; Wu, Y.; Yin, Y.; Yang, P.; Xia, Y., Single-crystalline nanowires of Ag₂Se can be synthesized by templating against nanowires of trigonal Se, *J. Am. Chem. Soc.* (2001) currently ASAP.
- Gosain, D.P.; Nakamura, M.; Shimizu, T.; Suzuki, M.; Okano, S., Nonvolatile memory based on reversible phase transition phenomena in telluride glasses, *Jap. J. Appl. Phys.* 28 (1989) 1013–1018.
- Guin, J.-P.; Rouxel, T.; Keryvin, V.; Sangleboeuf, J.-C.; Serre, I.; Lucas, J., Indentation creep of Ge–Se chalcogenide glasses below T_g: elastic recovery and non-Newtonian flow, *J. Non-Cryst. Solids* 298 (2002) 260–269.
- Guin, J.-P.; Rouxel, T.; Sangleboeuf, J.-C.; Melscoet, I.; Lucas, J., Hardness, toughness, and scratchability of germanium–selenium chalcogenide glasses, *J. Am. Ceram. Soc.* 85 (2002) 1545–52.
- Gupta, Y.P., On electrical switching and memory effects in amorphous chalcogenides, *J. Non-Cryst. Sol.* 3 (1970) 148–154.
- Haberland, D.R.; Stiegler, H., New experiments on the charge-controlled switching effect in amorphous semiconductors, *J. Non-Cryst. Solids* 8–10 (1972) 408–414.
- Haifz, M.M.; Ibrahim, M.M.; Dongol, M.; Hammad, F.H., Effect of composition on the structure and electrical properties of As–Se–Cu glasses, *J. Apply. Phys.* 54 (1983) 1950–1954.
- Hajto, J.; Rose, M.J.; Osborne, I.S.; Snell, A.J.; Le Comber, P.G.; Owen, A.E., Quantization effects in metal/a–Si:H/metal devices, *Int. J. Electronics* 73 (1992) 911–913.
- Hajto, J.; Hu, J.; Snell, A.J.; Turvey, K.; Rose, M., DC and AC measurements on metal/a–Si:H/metal room temperature quantised resistance devices, *J. Non-Cryst. Solids* 266–269 (2000) 1058–1061.
- Hajto, J.; McAuley, B.; Snell, A.J.; Owen, A.E., Theory of room temperature quantized resistance effects in metal–a–Si:H–metal thin film structures, *J. Non-Cryst. Solids* 198–200 (1996) 825–828.
- Hajto, J.; Owen, A.E.; Snell, A.J.; Le Comber, P.G.; Rose, M.J., Analogue memory and ballistic electron effects in metal–amorphous silicon structures, *Phil. Mag. B* 63 (1991) 349–369.
- Hayashi, T.; Ono, Y.; Fukaya, M.; Kan, H., Polarized memory switching in amorphous Se film, *Japan. J. Appl. Phys.* 13 (1974) 1163–1164.
- Hegab, N.A.; Fadel, M.; Sedeek, K., Memory switching phenomena in thin films of chalcogenide semiconductors, *Vacuum* 45 (1994) 459–462.

- Hirose, Y.; Hirose, H., Polarity-dependent memory switching and behavior of Ag dendrite in Ag-photodoped amorphous As₂S₃ films, *J. Appl. Phys.* 47 (1976) 2767–2772.
- Hong, K.S.; Speyer, R.F., Switching behavior in II–IV–V₂ amorphous semiconductor systems, *J. Non-Cryst. Solids* 116 (1990) 191–200.
- Hosokawa, S., Atomic and electronic structures of glassy Ge_xSe_{1-x} around the stiffness threshold composition, *J. Optoelectronics and Advanced Materials* 3 (2001) 199–214.
- Hu, J.; Snell, A.J.; Hajto, J.; Owen, A.E., Constant current forming in Cr/p+a-/Si:H/V thin film devices, *J. Non-Cryst. Solids* 227–230 (1998) 1187–1191.
- Hu, J.; Hajto, J.; Snell, A.J.; Owen, A.E.; Rose, M.J., Capacitance anomaly near the metal–non–metal transition in Cr–hydrogenated amorphous Si–V thin–film devices, *Phil. Mag. B.* 74 (1996) 37–50.
- Hu, J.; Snell, A.J.; Hajto, J.; Owen, A.E., Current-induced instability in Cr–p+a–Si:H–V thin film devices, *Phil. Mag. B* 80 (2000) 29–43.
- Izima, S.; Sugi, M.; Kikuchi, M.; Tanaka, K., Electrical and thermal properties of semiconducting glasses As–Te–Ge, *Solid State Comm.* 8 (1970) 153–155.
- Ishikawa, R.; Kikuchi, M., Photovoltaic study on the photo-enhanced diffusion of Ag in amorphous films of Ge₂S₃, *J. Non-Cryst. Solids* 35 & 36 (1980) 1061–1066.
- Iyetomi, H.; Vashishta, P.; Kalia, R.K., Incipient phase separation in Ag/Ge/Se glasses: clustering of Ag atoms, *J. Non-Cryst. Solids* 262 (2000) 135–142.
- Jones, G.; Collins, R.A., Switching properties of thin selenium films under pulsed bias, *Thin Solid Films* 40 (1977) L15–L18.
- Joullie, A.M.; Marucchi, J., On the DC electrical conduction of amorphous As₂Se₇ before switching, *Phys. Stat. Sol. (a)* 13 (1972) K105–K109.
- Joullie, A.M.; Marucchi, J., Electrical properties of the amorphous alloy As₂Se₅, *Mat. Res. Bull.* 8 (1973) 433–442.
- Kaplan, T.; Adler, D., Electrothermal switching in amorphous semiconductors, *J. Non-Cryst. Solids* 8–10 (1972) 538–543.
- Kawaguchi, T.; Maruno, S.; Elliott, S.R., Optical, electrical, and structural properties of amorphous Ag–Ge–S and Ag–Ge–Se films and comparison of photoinduced and thermally induced phenomena of both systems, *J. Appl. Phys.* 79 (1996) 9096–9104.
- Kawaguchi, T.; Masui, K., Analysis of change in optical transmission spectra resulting from Ag photodoping in chalcogenide film, *Jpn. J. Appl. Phys.* 26 (1987) 15–21.
- Kawasaki, M.; Kawamura, J.; Nakamura, Y.; Aniya, M., Ionic conductivity of Ag_x(GeSe₃)_{1-x} (0 < x <= 0.571) glasses, *Solid state Ionics* 123 (1999) 259–269.
- Kluge, G.; Thomas, A.; Klages, R.; Grotzschel, R., Silver photodiffusion in amorphous Ge_xSe_{100-x}, *J. Non-Cryst. Solids* 124 (1990) 186–193.
- Kolobov, A.V., On the origin of p-type conductivity in amorphous chalcogenides, *J. Non-Cryst. Solids* 198–200 (1996) 728–731.
- Kolobov, A.V., Lateral diffusion of silver in vitreous chalcogenide films, *J. Non-Cryst. Solids* 137–138 (1991) 1027–1030.
- Korkinova, Ts.N.; Andreichin, R.E., Chalcogenide glass polarization and the type of contacts, *J. Non-Cryst. Solids* 194 (1996) 256–259.
- Kotkata, M.F.; Afif, M.A.; Labib, H.H.; Hegab, N.A.; Abdel-Aziz, M.M., Memory switching in amorphous GeSeTe chalcogenide semiconductor films, *Thin Solid Films* 240 (1994) 143–146.
- Lakshminarayan, K.N.; Srivastava, K.K.; Panwar, O.S.; Dumar, A., Amorphous semiconductor devices: memory and switching mechanism, *J. Instn Electronics & Telecom. Engrs* 27 (1981) 16–19.
- Lal, M.; Goyal, N., Chemical bond approach to study the memory and threshold switching chalcogenide glasses, *Indian Journal of pure & appl. phys.* 29 (1991) 303–304.
- Leimer, F.; Stotzel, H.; Kottwitz, A., Isothermal electrical polarisation of amorphous GeSe films with blocking Al contacts influenced by Poole–Frenkel conduction, *Phys. Stat. Sol. (a)* 29 (1975) K129–K132.
- Leung, W.; Cheung, N.; Neureuther, A.R., Photoinduced diffusion of Ag in Ge_xSe_{1-x} glass, *Appl. Phys. Lett.* 46 (1985) 543–545.
- Matsushita, T.; Yamagami, T.; Okuda, M., Polarized memory effect observed on Se–SnO₂ system, *Jap. J. Appl. Phys.* 11 (1972) 1657–1662.
- Matsushita, T.; Yamagami, T.; Okuda, M., Polarized memory effect observed on amorphous selenium thin films, *Jpn. J. Appl. Phys.* 11 (1972) 606.
- Mazurier, F.; Levy, M.; Souquet, J.L., Reversible and irreversible electrical switching in TeO₂–V₂O₅ based glasses, *Journal de Physique IV* 2 (1992) C2–185–C2–188.
- Messoussi, R.; Bernede, J.C.; Benhida, S.; Abachi, T.; Latef, A., Electrical characterization of M/Se structures (M=Ni, Bi), *Mat. Chem. And Phys.* 28 (1991) 253–258.
- Mitkova, M.; Boolchand, P., Microscopic origin of the glass forming tendency in chalcogenides and constraint theory, *J. Non-Cryst. Solids* 240 (1998) 1–21.
- Mitkova, M.; Kozicki, M.N., Silver incorporation in Ge–Se glasses used in programmable metallization cell devices, *J. Non-Cryst. Solids* 299–302 (2002) 1023–1027.
- Mitkova, M.; Wang, Y.; Boolchand, P., Dual chemical role of Ag as an additive in chalcogenide glasses, *Phys. Rev. Lett.* 83 (1999) 3848–3851.
- Miyatani, S.-y., Electronic and ionic conduction in (Ag_xCu_{1-x})₂Se, *J. Phys. Soc. Japan* 34 (1973) 423–432.
- Miyatani, S.-y., Electrical properties of Ag₂Se, *J. Phys. Soc. Japan* 13 (1958) 317.
- Miyatani, S.-y., Ionic conduction in beta–Ag₂Te and beta–Ag₂Se, *Journal Phys. Soc. Japan* 14 (1959) 996–1002.
- Mott, N.F., Conduction in glasses containing transition metal ions, *J. Non-Cryst. Solids* 1 (1968) 1–17.
- Nakayama, K.; Kitagawa, T.; Ohmura, M.; Suzuki, M., Nonvolatile memory based on phase transitions in chalcogenide thin films, *Jpn. J. Appl. Phys.* 32 (1993) 564–569.
- Nakayama, K.; Kojima, K.; Hayakawa, F.; Imai, Y.; Kitagawa, A.; Suzuki, M., Submicron nonvolatile memory cell based on reversible phase transition in chalcogenide glasses, *Jpn. J. Appl. Phys.* 39 (2000) 6157–6161.
- Nang, T.T.; Okuda, M.; Matsushita, T.; Yokota, S.; Suzuki, A., Electrical and optical parameters of Ge_xSe_{1-x} amorphous thin films, *Jap. J. App. Phys.* 15 (1976) 849–853.
- Narayanan, R.A.; Asokan, S.; Kumar, A., Evidence concerning the effect of topology on electrical switching in chalcogenide network glasses, *Phys. Rev. B* 54 (1996) 4413–4415.
- Neale, R.G.; Aseltine, J.A., The application of amorphous materials to computer memories, *IEEE transactions on electron dev. Ed-20* (1973) 195–209.

- Ovshinsky S.R.; Fritzsche, H., Reversible structural transformations in amorphous semiconductors for memory and logic, *Mettallurgical transactions* 2 (1971) 641–645.
- Ovshinsky, S.R., Reversible electrical switching phenomena in disordered structures, *Phys. Rev. Lett.* 21 (1968) 1450–1453.
- Owen, A.E.; LeComber, P.G.; Sarrabayrouse, G.; Spear, W.E., New amorphous–silicon electrically programmable nonvolatile switching device, *IEE Proc.* 129 (1982) 51–54.
- Owen, A.E.; Firth, A.P.; Ewen, P.J.S., Photo-induced structural and physico-chemical changes in amorphous chalcogenide semiconductors, *Phil. Mag. B* 52 (1985) 347–362.
- Owen, A.E.; Le Comber, P.G.; Hajto, J.; Rose, M.J.; Snell, A.J., Switching in amorphous devices, *Int. J. Electronics* 73 (1992) 897–906.
- Pearson, A.D.; Miller, C.E., Filamentary conduction in semi-conducting glass diodes, *App. Phys. Lett.* 14 (1969) 280–282.
- Pinto, R.; Ramanathan, K.V., Electric field induced memory switching in thin films of the chalcogenide system Ge–As–Se, *Appl. Phys. Lett.* 19 (1971) 221–223.
- Popescu, C., The effect of local non-uniformities on thermal switching and high field behavior of structures with chalcogenide glasses, *Solid-state electronics* 18 (1975) 671–681.
- Popescu, C.; Croitoru, N., The contribution of the lateral thermal instability to the switching phenomenon, *J. Non-Cryst. Solids* 8–10 (1972) 531–537.
- Popov, A.I.; Geller, I.K.H.; Shemetova, V.K., Memory and threshold switching effects in amorphous selenium, *Phys. Stat. Sol. (a)* 44 (1977) K71–K73.
- Prakash, S.; Asokan, S.; Ghare, D.B., Easily reversible memory switching in Ge–As–Te glasses, *J. Phys. D: Appl. Phys.* 29 (1996) 2004–2008.
- Rahman, S.; Sivarama Sastry, G., Electronic switching in Ge–Bi–Se–Te glasses, *Mat. Sci. and Eng. B12* (1992) 219–222.
- Ramesh, K.; Asokan, S.; Sangunni, K.S.; Gopal, E.S.R., Electrical Switching in germanium telluride glasses doped with Cu and Ag, *Appl. Phys. A* 69 (1999) 421–425.
- Rose, M.J.; Hajto, J.; Lecomber, P.G.; Gage, S.M.; Choi, W.K.; Snell, A.J.; Owen, A.E., Amorphous silicon analogue memory devices, *J. Non-Cryst. Solids* 115 (1989) 168–170.
- Rose, M.J.; Snell, A.J.; Lecomber, P.G.; Hajto, J.; Fitzgerald, A.G.; Owen, A.E., Aspects of non-volatility in a –Si:H memory devices, *Mat. Res. Soc. Symp. Proc. V* 258, 1992, 1075–1080.
- Schuoocker, D.; Rieder, G., On the reliability of amorphous chalcogenide switching devices, *J. Non-Cryst. Solids* 29 (1978) 397–407.
- Sharma, A.K.; Singh, B., Electrical conductivity measurements of evaporated selenium films in vacuum, *Proc. Indian Natn. Sci. Acad.* 46, A, (1980) 362–368.
- Sharma, P., Structural, electrical and optical properties of silver selenide films, *Ind. J. Of pure and applied phys.* 35 (1997) 424–427.
- Snell, A.J.; Lecomber, P.G.; Hajto, J.; Rose, M.J.; Owen, A.E.; Osborne, I.L., Analogue memory effects in metal/a–Si:H/metal memory devices, *J. Non-Cryst. Solids* 137–138 (1991) 1257–1262.
- Snell, A.J.; Hajto, J.; Rose, M.J.; Osborne, L.S.; Holmes, A.; Owen, A.E.; Gibson, R.A.G., Analogue memory effects in metal/a–Si:H/metal thin film structures, *Mat. Res. Soc. Symp. Proc. V* 297, 1993, 1017–1021.
- Steventon, A.G., Microfilaments in amorphous chalcogenide memory devices, *J. Phys. D: Appl. Phys.* 8 (1975) L120–L122.
- Steventon, A.G., The switching mechanisms in amorphous chalcogenide memory devices, *J. Non-Cryst. Solids* 21 (1976) 319–329.
- Stocker, H.J., Bulk and thin film switching and memory effects in semiconducting chalcogenide glasses, *App. Phys. Lett.* 15 (1969) 55–57.
- Tanaka, K., Ionic and mixed conductions in Ag photodoping process, *Mod. Phys. Lett B* 4 (1990) 1373–1377.
- Tanaka, K.; Iizima, S.; Sugi, M.; Okada, Y.; Kikuchi, M., Thermal effects on switching phenomenon in chalcogenide amorphous semiconductors, *Solid State Comm.* 8 (1970) 387–389.
- Thornburg, D.D., Memory switching in a Type I amorphous chalcogenide, *J. Elect. Mat.* 2 (1973) 3–15.
- Thornburg, D.D., Memory switching in amorphous arsenic triselenide, *J. Non-Cryst. Solids* 11 (1972) 113–120.
- Thornburg, D.D.; White, R.M., Electric field enhanced phase separation and memory switching in amorphous arsenic triselenide, *Journal(?)* (1972) 4609–4612.
- Tichy, L.; Ticha, H., Remark on the glass-forming ability in $\text{Ge}_x\text{Se}_{1-x}$ and $\text{As}_x\text{Se}_{1-x}$ systems, *J. Non-Cryst. Solids* 261 (2000) 277–281.
- Titus, S.S.K.; Chatterjee, R.; Asokan, S., Electrical switching and short-range order in As–Te glasses, *Phys. Rev. B* 48 (1993) 14650–14652.
- Tranchant, S.; Peytavin, S.; Ribes, M.; Flank, A.M.; Dexpert, H.; Lagarde, J.P., Silver chalcogenide glasses Ag–Ge–Se: Ionic conduction and exafs structural investigation, Transport-structure relations in fast ion and mixed conductors Proceedings of the 6th Riso International symposium. Sep. 9–13, 1985.
- Tregouet, Y.; Bernede, J.C., Silver movements in Ag_2Te thin films: switching and memory effects, *Thin Solid Films* 57 (1979) 49–54.
- Uemura, O.; Kameda, Y.; Kokai, S.; Satow, T., Thermally induced crystallization of amorphous $\text{Ge}_{0.4}\text{Se}_{0.6}$, *J. Non-Cryst. Solids* 117–118 (1990) 219–221.
- Uttecht, R.; Stevenson, H.; Sie, C.H.; Griener, J.D.; Raghavan, K.S., Electric field induced filament formation in As–Te–Ge glass, *J. Non-Cryst. Solids* 2 (1970) 358–370.
- Viger, C.; Lefrancois, G.; Fleury, G., Anomalous behaviour of amorphous selenium films, *J. Non-Cryst. Solids* 33 (1976) 267–272.
- Vodenicharov, C.; Parvanov, S.; Petkov, P., Electrode-limited currents in the thin-film M–GeSe–M system, *Mat. Chem. And Phys.* 21 (1989) 447–454.
- Wang, S.-J.; Misium, G.R.; Camp, J.C.; Chen, K.-L.; Tigelaar, H.L., High-performance Metal/silicide antifuse, *IEEE electron dev. Lett.* 13 (1992) 471–472.
- Weirauch, D.F., Threshold switching and thermal filaments in amorphous semiconductors, *App. Phys. Lett.* 16 (1970) 72–73.
- West, W.C.; Sieradzki, K.; Kardynal, B.; Kozicki, M.N., Equivalent circuit modeling of the $\text{Ag}[\text{As}_{0.24}\text{S}_{0.36}\text{Ag}_{0.40}]/\text{Ag}$ System prepared by photodissolution of Ag, *J. Electrochem. Soc.* 145 (1998) 2971–2974.

West, W.C., Electrically erasable non-volatile memory via electrochemical deposition of multifractal aggregates, Ph.D. Dissertation, ASU 1998.

Zhang, M.; Mancini, S.; Bresser, W.; Boolchand, P., Variation of glass transition temperature, T_g , with average coordination number, $\langle m \rangle$, in network glasses: evidence of a threshold behavior in the slope $|dT_g/d\langle m \rangle|$ at the rigidity percolation threshold ($\langle m \rangle = 2.4$), *J. Non-Cryst. Solids* 151 (1992) 149–154.

“1. Programmable Metallization Cell Technology Description,” Michael N. Kozicki, Feb. 18, 2000.

“Programmable Metallization Cell,” Michael N. Kozicki, Axon Technologies Corp. and Arizona State University, Presentation to Micron Technology, Inc., Apr. 6, 2000.

* cited by examiner

FIG. 1




FIG. 3




FIG. 4




FIG. 5





FIG. 6



1

COMPLEMENTARY BIT PCRAM SENSE AMPLIFIER AND METHOD OF OPERATION

FIELD OF THE INVENTION

The invention relates to a method and apparatus for sensing the resistance of a Programmable Conductor Random Access Memory (PCRAM) element.

BACKGROUND OF THE INVENTION

PCRAM devices store binary data as two different resistance values, one higher than the other. The resistance value represents a particular binary value of logic "0" or logic "1". When sensing the resistance value of a PCRAM device, it is common to compare the resistance of a memory cell undergoing a read operation with resistance of a reference cell to determine the resistance value of the cell being read and thus its logic state. Such an approach is disclosed in U.S. Pat. No. 5,883,827. However, this approach has some limitations.

If the reference cell is defective and a column of memory cells within an array uses a same defective reference cell, the entire column of memory cells will have erroneous resistance readings. In addition, specialized circuitry is required to write a resistance value into the reference cell, and a sense amplifier circuit for such an arrangement tends to be complex and large.

Typically, sensing schemes for PCRAM devices also tend to have a unique architecture which is different from that normally employed in typical DRAM circuits. Although PCRAM's differ from DRAM's in that they store binary values in resistive memory elements rather than as charges on capacitors, and although PCRAM's are non-volatile, where the capacitor structures employed in DRAM's are volatile, nevertheless it would be desirable if the read and write circuits for both devices were as similar as possible so that existing DRAM memory device architectures could be easily adapted to read and write PCRAM devices.

BRIEF SUMMARY OF THE INVENTION

The present invention provides a PCRAM memory device and its method of operation which utilizes a read architecture similar to that employed in some DRAM memory devices. A pair of complementary PCRAM memory cells comprising first and second programmable conductor memory elements are employed, each connected to respective access transistors. During a write operation, the first and second memory elements are written with complementary binary values, that is: if the first memory element is written to a high resistance state, then the second memory element is written to a low resistance state; whereas if the first memory element is written to a low resistance state, the second memory element is written to a higher resistance state.

During a read operation of, for example, the first memory element, a sense amplifier is connected so that its respective inputs are coupled to receive respective precharge voltages which discharge through the first and second memory elements. A sense amplifier reads the discharging voltages through the two memory elements to determine which is the larger voltage, thus determining the resistance (high or low) and logic state (high or low) of the memory cell being read.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other features and advantages of the invention will become more apparent from the following detailed

2

description of exemplary embodiments of the invention which are provided in connection with the accompanying drawings in which:

FIG. 1 shows an exemplary PCRAM device;

FIG. 2 is a schematic diagram depicting one aspect of the invention;

FIG. 3 is a schematic diagram depicting an additional aspect of the invention;

FIG. 4 is a schematic diagram depicting an additional aspect of the invention;

FIG. 5 shows the discharge rate characteristics of capacitors employed in the invention;

FIG. 6 shows the invention utilized in a computer system.

DETAILED DESCRIPTION OF THE INVENTION

The present invention employs a sense amplifier architecture which is somewhat similar to that employed in some conventional DRAM devices to sense the resistance states of PCRAM memory cells. In the invention, a binary value is stored as a resistance value in a first PCRAM cell while its complement resistance value is stored in a second PCRAM cell. During readout of the first PCRAM cell, both PCRAM cells are used to discharge a precharge voltage into respective inputs of a sense amplifier which reads the discharge voltages to determine the resistance and thus the binary value stored in the first PCRAM cell undergoing a read operation.

FIG. 1 illustrates an exemplary cell arrangement provided within a portion of a PCRAM memory device constructed in accordance with the invention. A PCRAM memory element **102** is illustrated which has a chalcogenite glass body and lower **103** and upper **104** conductors. As is well known, a programmable conductor memory element has two stable resistance states: one high resistance and one low resistance. Normally, when at rest the memory has a high resistance state, but it can be programmed to a low resistance state by suitably applying bias voltages to the conductors **103** and **104**. Typically, the low resistant state of a PCRAM memory element is characterized by a dendrite growth through the chalcogenite glass body or along the surface of the chalcogenite glass body between the conductors **103** and **104**. A high resistant state is present when there is no such dendrite growth. The grown dendrite is relatively non-volatile in that it will remain in place for a relatively long time, e.g. days or weeks, after the bias voltage is removed.

As further shown in FIG. 1, the PCRAM memory element **102** is coupled by a conductive plug **101** to an access transistor **207** which is driven by a word line **105** which forms the gate structure of transistor **207**. The access transistor is coupled through conductive plug **101** to one of the conductors **103** of the PCRAM memory element. The other conductor **104** of the PCRAM element is connected by a common cell plate **109** to a bias voltage, which is common to other PCRAM memory elements provided in the memory device.

FIG. 1 illustrates a common PCRAM architecture in which two adjacent memory cells **207**, **211** are coupled to a common digit line **118**. Thus, FIG. 1 also shows another access transistor **211** driven by a word line **107** which is connected through conductive plug **99** to another PCRAM memory element **104**, which in turn is also connected also to the common cell plate **109**. Access transistor **211** also has one terminal connected to digit line **118**.

FIG. 2 shows an electrical schematic arrangement of a memory array employing the cell architecture illustrated in

FIG. 1. Thus, the top portion of FIG. 2 illustrates the transistors 207 and 211 coupled to the respective PCRAM memory elements 102 and 106 with the access transistors 207 and 211 coupling the memory elements 102 and 106 to the digit line 118.

As also illustrated in FIG. 2, a complementary digit line D1* 120 is also provided in the memory array, to which another set of access transistors is connected which are in turn connected to other PCRAM memory elements. To simplify discussion, a single complementary pair of PCRAM cells is illustrated as 300. It includes transistor 207 and associated PCRAM memory element 102, which is coupled to the digit line 118 (D1), and an access transistor 209 and associated PCRAM memory element 124, which are coupled to digit line 120 (D1*).

During a write operation, a row line 104, which is coupled to transistor 207 and a row line 113 which is coupled to transistor 209 are activated such that if PCRAM memory element 102 is written to a high resistance state, PCRAM element 124 is written to a low resistance state, and vice versa. In this way, PCRAM memory elements 102 and 124 are accessed together and always store complementary resistance digit values. Thus assuming that PCRAM memory element 102 is the primary element which is being written to and read from, a sense amplifier 210 which is coupled to the digit lines 118 and 120 will read the value of PCRAM memory element 102 by comparing a discharging precharge voltage on digit line 118 to the discharging precharge voltage on digit line 120 during a memory read operation.

Thus, prior to a memory read, a precharge voltage is applied to complementary digit lines 118 and 120 by a precharge circuit 301. The precharge circuit is activated by a logic circuit on a precharge line which activates transistors 305 to supply a voltage, for example, $V_{cc}/2$, to both digit lines 118 and 120.

An equilibrate circuit 303 may also be provided which is activated by an equilibrate signal after the precharge circuit is activated to ensure that the voltages on lines 118 and 120 are the same. The voltages on lines 118 and 120 are held by a parasitic capacitance of the lines. After precharge and equilibrate (if present) circuits are activated, a read operation may be conducted on the complimentary cell pair 300. This read operation is illustrated in greater detail in FIG. 3, which is a simplification of the sense amplifier 210 input path.

Parasitic capacitance for the complementary digit lines 118 and 120 are illustrated as C1 and C1*. The respective access transistors 207 and 209 are illustrated as connected to their respective word lines 105 and 113. The PCRAM memory elements 102 and 124 are also illustrated. As noted, a binary value is stored, for example, in memory PCRAM memory element 102 as a resistance value. It will be either a high resistance value or a low resistance value, and the complementary resistance value will be stored in PCRAM memory element 124.

During a read operation, the precharge voltage applied to the complementary digit lines 118 and 120 is allowed to discharge through the access transistors 207 and 209 and through the respective resistance values of the PCRAM memory elements 102 and 124. Because the resistance values will be different, one high and one low, the voltages on the digit lines D1 and D1* (118, 120) will begin to diverge during a read operation. Although the voltage initially applied to the complementary digit lines 118 and 120 is a voltage of $V_{cc}/2$, during a read operation this voltage actually is slightly higher by approximately 0.3 mV due to the presence of the parasitic capacitance C1 and C1* on the

digit lines 118 and 120, as well as gate-drain capacitance inherent within transistors 207 and 209.

FIG. 5 illustrates the voltages on the complementary digit lines 118 and 120 during a read operation. The activation of the word lines 105 and 113 is illustrated as a pulse signal, and initially the voltage of $V_{cc}/2$ approximately 0.3 mV which exists on both digit lines D1 and D1* begins to decay. Because one PCRAM memory element, e.g. 102, has a higher resistance than the other, the voltage on the digit line associated with the lower resistance value, e.g. 124, will decay faster than the voltage on the digit line coupled to the higher resistance value, e.g. D1. This is illustrated in FIG. 5.

The divergence of the two voltages on the lines D1 and D1* progressively increases. At a predetermined time after the word lines 105 and 113 are activated, the sense amplifier 210 is activated. The sense amplifier can have an architecture typically employed in a DRAM arrangement which is illustrated in FIG. 4. Such a sense amplifier includes an Nsense amplifier latch 302 and a Psense amplifier latch 304. This structure is illustrated in FIG. 4.

Reverting back to FIG. 5, the N sense amplifier is fired first at a time t_1 . When the Nsense amplifier fires, the digit line which has the lower voltage, e.g. D1* in the example, is immediately pulled to ground. Thereafter, the Psense amplifier is fired at a time t_2 which drives the higher voltage line, e.g. D1, to V_{cc} . Accordingly at a time t_2 , the sense amplifier 210 outputs a value of V_{cc} indicating the high resistant state for the PCRAM memory element 102.

Although FIG. 5 illustrates the signal timing which occurs when PCRAM memory element 102 has a higher resistance than memory element 104, obviously the signal levels are reversed if PCRAM memory element 102 has a low resistance state and PCRAM memory element 124 has a high resistance state. That is, the signal diagrams illustrated in the FIG. 5 would have the digit line D1* going towards V_{cc} and the digit line D1 going towards ground.

FIG. 5 also illustrates another aspect of the invention. As shown, the voltage for row lines 105, 113 increases from near ground level to a positive voltage near V_{cc} for a read operation. This voltage then returns to near ground level before the sense amplifier is enabled (before t_1). As a result, there is no rewriting of a read PCRAM memory element. If such rewriting of a PCRAM cell is desired, then the voltage on row line 105, 113 having a memory element which is written to a low resistance state, may be at a voltage level near V_{cc} during operation of the sense amplifier 210, which will automatically rewrite (refresh) the read cell to the low resistance state.

Because programmable contact memory elements are resistive rather than capacitive memory elements, it is possible they will take longer to pull the digit lines up to V_{cc} and to ground than a typical capacitive memory element found within a DRAM. Supposing that to be true, older DRAM sense amplifier designs that run somewhat slower than the latest generation of DRAM sense amplifiers could also be used with PCRAM memory cells. The advantage of doing so would be that these older DRAM sense amplifiers have already been shown to perform effectively, and their test infrastructure is already confirmed. Consequently, a hybrid memory consisting of PCRAM memory elements using DRAM sense amplifiers can be produced having the advantages of PCRAM technology, yet being producible quickly and inexpensively.

Although FIG. 2 shows the complementary programmable contact memory element 102 and 106 and associated access transistors and digit lines D and D* as being provided

5

in the same memory array, the complementary memory elements, access transistors and digit lines may also be provided in respective different memory arrays.

FIG. 6 is a block diagram of a processor-based system 400 utilizing a PCRAM memory device 200 constructed in accordance with one of the embodiments of the present invention. The processor-based system 400 may be a computer system, a process control system or any other system employing a processor and associated memory. The system 400 includes a central processing unit (CPU) 402, e.g., a microprocessor, that communicates with the PCRAM memory device 408 and an I/O device 404 over a bus 420. It must be noted that the bus 420 may be a series of buses and bridges commonly used in a processor-based system, but for convenience purposes only, the bus 420 has been illustrated as a single bus. A second I/O device 406 is illustrated, but is not necessary to practice the invention. The processor-based system 400 also includes read-only memory (ROM) 410 and may include peripheral devices such as a floppy disk drive 412 and a compact disk (CD) ROM drive 414 that also communicates with the CPU 402 over the bus 420 as is well known in the art.

One or more memory devices 200 may be provided on a plug-in memory module 256, e.g. SIMM, DIMM or other plug-in memory module, for easy connection with or disconnection from the bus 420. While the invention has been described and illustrated with reference to specific exemplary embodiments, it should be understood that many modifications and substitutions can be made without departing from the spirit and scope of the invention. Accordingly, the invention is not to be considered as limited by the foregoing description but is only limited by the scope of the appended claims.

What is claimed as new and desired to be protected by Letters Patent of the United States is:

1. A method of operating a programmable conductor memory device comprising:

storing a binary value as respective resistance states in a first and second programmable conductor memory element wherein the resistance state stored in the first programmable conductor memory element is complementary to the resistance state concurrently stored in the second programmable conductor memory element;

determining a binary value stored in one of said programmable conductor memory elements by discharging respective voltages through said memory elements and comparing the discharging voltages; and

rewriting the binary value stored only in the one of said first and second programmable conductor memory elements which is storing a low resistance state.

2. A method as in claim 1 wherein said discharging comprises:

precharging complementary digit lines to a voltage value; and

respectively discharging the voltage value on each of said complementary digit lines through said first and second programmable conductor memory elements.

3. The method as in claim 2 wherein said precharged voltage value on said complementary digit lines is discharged through said respective first and second program-

6

mable conductor memory elements by enabling access transistors respectively associated with each of said memory elements.

4. The method as in claim 3 further comprising completing said precharge before enabling said access transistors.

5. The method as in claim 4 further comprising equilibrating said digit lines before enabling said access transistors.

6. The method as in claim 3 where said comparison comprises:

determining whether the discharging voltage associated with one memory element is the higher or lower of the two discharging voltages and outputting a first binary value if the discharging voltage associated with the said one memory element is the higher voltage and outputting a second binary value if the discharging voltage associated with said one memory element is the lower voltage.

7. The method as in claim 6 further comprising setting a digit line having a higher discharge voltage to a first predetermined voltage state and setting a digit line having a lower discharging voltage to a second predetermined voltage state.

8. The method as in claim 7 wherein said first predetermined voltage is higher than said second predetermined voltage.

9. The method as in claim 8 wherein said second predetermined voltage is ground voltage.

10. The method as in claim 7 further comprising disabling said access transistors before said digit lines are set to said first and second voltage states.

11. The method as in claim 7 further comprising enabling at least one of said access transistors during a time when said digit lines are set to said first and second voltage states.

12. The method as in claim 1, wherein said act of rewriting comprises:

increasing a voltage level of a rowline coupled to said one programmable conductor memory element from approximately ground level to approximately a system voltage level during operation of a sense amplifier circuit used in performing said act of determining.

13. A method of operating a programmable conductor memory device comprising:

storing a binary value as respective resistance states in a first and second programmable conductor memory element wherein the resistance state stored in the first programmable conductor memory element is complementary to the resistance state concurrently stored in the second programmable conductor memory element;

determining a binary value stored in one of said programmable conductor memory elements by discharging respective voltages through said memory elements and comparing the discharging voltages; and

maintaining a voltage level of a wordline coupled to each of said first and second programmable conductor memory elements at approximately ground during activation of a sense amplifier used to perform said act of determining.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,791,859 B2
DATED : September 14, 2004
INVENTOR(S) : Glen Hush et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 2,
Lines 33, 42 and 42-43, replace "chalcogenite" with -- chalcogenide. --

Signed and Sealed this

Twenty-fifth Day of January, 2005

A handwritten signature in black ink on a light gray dotted background. The signature reads "Jon W. Dudas" in a cursive style.

JON W. DUDAS
Director of the United States Patent and Trademark Office